

BRUSHLESS MOTOR

18V 3000mAh
Li-Ion BATTERY

400KGS

ZP96

PATENTED STRAP GRIPPERS

ZAPAK[®]

**HIGH TENSION BATTERY POWERED PLASTIC STRAPPING TOOL
ZP92 / ZP96**

FEATURES

Latest technology

- **Brushless motor-ZAPAK** patented single motor design provides extremely long service life.
- **Li-Ion battery**-18V 3000mAh high capacity rechargeable battery and **Bosch** 30 minutes charger.

Powerful & Speedy

- Max. tension 400 kg (4000N) - **ZP96 heavy duty** model.
- Max. tension 250 kg (2500N) - **ZP92 standard duty** model.
- **Patented strap grippers design** contributes to high tension ability.
- **One-handed operation** performs automatic tensioning, friction welding and cutting efficiently.

Smart & Easy

- **Pre-programmed touch panel** with digital signal to suit different operation needs instinctively.
- **Lightest** model in same class of tools. Approx. 3.5kg only (7.7 lbs incl. battery). Relieves operation fatigue.
- Special tool retreating device ensures smooth and **easy removal of tool**.
- **Unique rear-end roller** design prevents scratches or worn out damages on strapping objects.
- **User self-adjustable strap widths guiders** and self-changeable wearing parts.
- **Optional hanger** reduces operation fatigue.
- **Soft mode** device facilitates lighter strapping tension force for light packages or fragile objects.

Safety

- One-handed operation **conforms to CE safety directive** and meets RoHS requirements.
- Li-Ion battery **complies with UN38.3** safety requirements.

SPECIFICATION

Model No.	Fits Poly-Strap	Strap Width		Strap Thickness		Tension Range	Sealing Efficiency	Dimension	Tool Weight	Battery Weight
		mm	inch	mm	inch					
ZP92	PP	9~16	3/8	0.60	0.024	25~250 kg (55~550 lbs)	85 ± 5%	Approx. 33 x 15 x 12.5 cm (13 x 6 x 5 inch)	Approx. 3.5 kg / 7.7 lbs	Approx. 0.6 kg / 1.32 lbs
	PET		5/8	1.27	0.05					
ZP96	PP	16 & 19	5/8 & 3/4	0.65	0.026	50~400 kg (110~880 lbs)	85 ± 5%	Approx. 33 x 15 x 12.5 cm (13 x 6 x 5 inch)	Approx. 3.5 kg / 7.7 lbs	Approx. 0.6 kg / 1.32 lbs
	PET		1.27	0.05						

- Bosch charger A/C voltage 100V, 115V, 230V, 240V available for different markets demand.
- Sealing time adjustment: 0.4 ~ 3.6 seconds.
- Li-Ion battery life is up to 2000 charges with proper charging and discharging habits.
- Fully charged Li-Ion battery supports up to max. 400 cycles dependant on straps set tension & sealing time.

<Remarks>

- ◆ Tension performance and sealing efficiency varies based on battery capacity, strap specifications & quality.
- ◆ Soft or thin pp straps may require different cutter. Please consult with your dealer.

DISTRIBUTOR



©2011 Pantech International Inc. All rights reserved.
Worldwide Patented.
Printed in Taiwan, R.O.C.
ZAPAK is a registered trademark of Pantech International Inc.
Product and specifications subject to change without notice.
One Year limited manufacturer warranty.



P/N 92XX102A